Fission Resource Expansion Program Hits Wide Mineralization in all 20 Holes

written by Raj Shah | April 7, 2021 April 7, 2021 (<u>Source</u>) —

All Holes Intersect Multiple Stacked Intervals; 13 Holes Hit High Grade Mineralization

FISSION URANIUM CORP. ("Fission" or "the Company") is pleased to announce results from the first of its 2021 drill programs on the R780E zone of the high-grade Triple R deposit at its' PLS project, in the Athabasca Basin region of Saskatchewan, Canada. Twenty holes were completed in 7,147.8m, including 1 hole restarted due to excessive deviation. All twenty holes hit wide mineralization in multiple stacked intervals, with thirteen intercepting significant intervals of >10,000 cps radioactivity. The goal of the winter program was to upgrade key sections of the Triple R deposit's R780E zone to "indicated" category by increasing drill hole density where the resource is largely classified as Inferred. These recently completed holes have the potential to increase the Indicated category resource which may positively impact the planned feasibility study. The holes include PLS21-606 (line 900E), which intersected 118.0m of total composite mineralization, including 1.35m of total composite radioactivity >10,000 cps (with a peak of 23,400 cps) and PLS21-597 (line 900E) with 92.0m total composite mineralization, including 4.80m total >10,000 cps (with a peak of 51,400 cps).

Ross McElroy, CEO for Fission, commented, "This is the first of our 2021 drill programs and I'm very pleased to report that we

have met, and in numerous instances exceeded, our expectations on width and strength of mineralization in all 20 holes. We continue to make strong progress towards feasibility, and these results will be instrumental in delivering a key part of our deposit growth strategy."

Drilling Highlights

- 20 Holes Hit Significant Mineralization over wide Intervals. 21 holes were drilled (7,147.8m) including 20 holes completed (7,046.8m) with 1 abandoned and redrilled due to deviation from target.
- Triple R Deposit Resource Drilling. Drilling successfully targeted an important mainly "inferred" categorized area of the eastern R780E zone between lines 900E and 1125E, using step out and infill drilling to achieve spacing of ~15m x 20m (horizontal / vertical), with the aim of conversion from Inferred to Indicated.
- Hole PLS21-597 (line 900E)
 - 92.0m total composite mineralization over a 214m interval (between 117.0m to 331.0m), including
 - 4.8m of total composite mineralization >10,000cps
- Hole PLS21-605 (line 930E)
 - 110.0m total composite mineralization over a 272.5m interval (between 105.5m to 378.0m), including
 - 4.15m of total composite mineralization >10,000 cps
- Hole PLS21-595 (line 1050E)
 - •46.0m total composite mineralization over a 73.5m interval (between 264.0m to 337.5m), including
 - 4.75m of total composite

mineralization >10,000 cps

Table 1: Drill Hole Summary

reals ID	-	Grid Line	Al	Dip	From (H)	30 (M)	Results On Min HUM minimum Minimum (M)	maliani Dribum (*100 upa m) CP3 Fluix Range	Lake Depth (re)	From . To (m)	Example Silvership (Apple Sinc)	Could be a
PES21492 PER21495A	ROSSE PURSON	HOSE HOME	354	42.1		046 Pole Abando 192 3 203 5	end Dear to Even	1	83	NA.	93	1913 2073
					96.5 97.6 29.5 29.5 29.0 29.0 29.0 29.0 29.0 20.5 20.0 20.0 20.0 20.0 20.0 20.0 20	200 8 200 8 200 8 200 9 200 9	20 15 315 38 38 30 35 20 18 88 45 50 25 25 20	330 - 640 641 - 740 320 - 27300				
PL521-000 F	FFNE	1996	555	40.4	2015 2015 2015	263	140	-900 - 2000 309 800 - 1700	82	84.	748	293.3
					2611 2611 2714	265.0 274.0 262.5	15 65 45	779 - 3400 -300 - 790 -300 - 940				
					2615 2615 2013	298.5 302.8 309.5	59 25 29	420 - 12250 420 - 1100 330 - 410				
	F7705	1005	107	-76.6	361.6 361.6	307 A 366 9	01 01	69 53 311-40	92	84	885	291.9
R321-994 K					341.6 151.0 188.0 188.6 161.0 161.0 161.0 161.0 161.0 162.0 162.0 163.0	158.5 158.5 162.0	05 20 10 10 20 15 05 10 08 30 20 15 25 08 10 10 10 10 10 10 10 10 10 10 10 10 10	996 - 2000 336 - 660 346 - 6050				
					164.0 161.0 162.0	165.5 161.5 160.0	15 05 10	334 - 1290 348 300 - 360				
					911 964 3624	190.0 199.0 294.0	08 50 20	300 600 - 11400 300 - 1300				
					265.6 263.5 296.3	296.5 296.8 287.8	15 25 03	430 - (m) 401 - 1900 603				
1521-016	FFINE	1996	100	-40	264.6 272.6	209.8 209.8	69 10	530 - 1400 330 - 12500 330 - 2700	79	84	72.7	363.8
					367.6 367.6 367.6	384.8 387.6 307.5	800 01 05 05 01 100 45 100 00 10 00 01	-300 - 60000 610 900				
PL321-099	P7906	1000	307	-10	175.0 165.0 186.0	183.5	01 130	300 - 400	62		7.1	200.9
					294.0 294.5	207.5 227.8 239.5	150	+300 - 500 +300 - 19400 +300 - 3400				
					296.5 296.5	209.0 200.5	69	718 718 400-99				
PLED LINE	PETON	1000	336	.01.6	322.6 10.8	322.5 188.6		379	42	N.	61	363.8
					101.0	100.5	05 1.5 10 05 10 12 10 10 10 10 10 10 10 10 10 10 10 10 10	340				
					927.6 577.6	184.5	10 10	430 - 710 360 - 25000				
					217.6	293	10	5301-0000 431-2700				
					2014 2415 Na 5	258.5 258.5	60 80 90	-300 - 36300 -300 - 42300 -300 - 5300				
					2935	296.5	20	-001-300 -001-000				
PL321-090	F790E	18905	307	-40	3364 953 944	105.5	20	500 - 640 - 500 - 640	82	84	88.3	258.9
					264 6 266 6 277 6	205.5	05	210 - 1100 498 500 - 1100				
					2716 2916 2016	290.5 290.3 307.5	05 20 05 10 05 10 105 10	-300 -629 896 - 1200 -300 -6200				
					200.0 207.6	504.0 502.0 564.5	10	430 - 620 534 - 2600 334 - 760				
PLECIARE I	PTIOR	WEST	140	л	101.6 101.6 176.6	1074 1735 1795	08 78 59	1000 -300 - 7200 -300 - 790	13	NA.	86.4	326.0
					102.6 105.5 107.6	1943 1913 2143	50 08 75 50 20 20 21 170	1000 1200 1200 1200 1200 1200 1200 1200				
					221.6 266.5 361.5	204.0 250.0 264.0	9.5	410 - 2000 500 - 200 - 2000				
PER21400	PTICE	1000	337	48.1	1915 CH 6	1040 1025 1793	18 80 05	30.1100 -300.2750 5-9	,	84.	66.3	3743
					3815 THE ST 1915 T	Section Sect	25 38 80 05 20 40 80 18 15 05 15 10 38 205 25 25 20 00	294 - 679 - 300 - 1900 - 300 - 30100				
					201.0 247.0 221.5	206.6 268.5 202.9	18 15 05	390 - 26200 300 - 430 468				
					2365 2316 2366	229.9 232.9 238.5	15 10 38	626 - 1000 3606 - 4200 -300 - 6700				
					2914 274.5 297.5	271.5 295.9 300.9	12.5 29.5 2.5	-300 - 57000 -300 - 55000 3 10 - 650				
					311.0 311.0 347.0	265.9 268.5 260.3	20 03 30 150	-300 - 740 940 330 - 450				
L421-661	MINE	9196	100	.00.4	165 163 163	100.5 147.5 186.0	20 18	-300 - 5000 370 - 1200 -300 - 420	82		6.1	377.8
					2014 2015	265 265 269	20 18 25 65 25 20 20 20 25	-300 -5100 500				
					2016 2016 2016	271.0 200.5 200.5	20 20 20	270 - 460 260 - 6100 4300 - 420				
					300 3316 3345	329.5 309.5 309.5	10	-901 - 2290 400 301 - 30 ⁿ				
PL521-002	FFME	9100	557	-76.4	376.0 96.5 106.0	276.2 100.3 100.5	05 05	60 - 500 500 400	62	84	93	362.8
					1343 1766 1866	967.5 186.2 186.2 186.2 186.5 295.5	10 05 05 10 10 03 60 10 10 10 10 10 10 10 10 10 10 10 10 10	-300 - 300 -300 - 300 -300 - 1500				
					206.5 224.5 228.5	292.5 202.5 290.5	10	-300 - 1730 500 - 500 -300 - 14000				
					266 B 266 B 266 B	255.5 269.9 324.9	10. 16.6 36.0	-300 - 3200 -300 - +68556 -300 - 12500				
PLE21485	PENDE	1100	330	.01.1	342.6 372.6 86.4	547.5 572.5 100.5	55 65 28	-900 - 1500 259 360 - 640	62	NL	0.1	363.8
					3726 86.6 191.8 194.6 196.5 196.3 196.4 176.6 221.6 22	100.5 100.5 154.3	05 55 55	538 426 - 5800 -300 - 510				
					196.5 102.6 172.6	100.5 100.5 105.5	10	100 - 100 200 - 100 - 100				
					2416 2216 2316	253 253 263	10 40 93	5301 - 20000 -300 - 3000 -300 - 1700				
					2945 2945	256.9 256.9	40 65	470 - 33000 470 - 33000 390 - 43200				
					361.0	972.5 100.6 100.5 100.5 100.5 100.0	05 25 05 55 55 10 10 10 40 20 81 40 05 55 10 40 10 11 40 10 10 10 10 10 10 10 10 10 10 10 10 10	1				
SELV.	Bira	per-	1		337.6	109.9 108.5 546.9	15 05	390 - 170 540	12		277	
1404	r/108	-	120	-813	345.5 101.6 171.6 201.5 241.0 257.6 261.0	3653 1023 1063 2073 205 205 2063 2063 2063 2063 2063 2063 2063 2063	05 08 285 05 05 05 00 00	330 - 255 540 400 -300 - 1550 -300 - 1500 -300 - 1500 -300 - 300 -300	12		63	3543
					257.6 267.6 268.6 278.4	290.5 274.5 280.5	35 63 63	-300 - 1500 -300 - 1600 300				
					361.6 361.5 261.6	2943 2943 3023	05 75 40					
					378.0 323.0 332.0	209.5 229.5 229.5	05 75 40 03 43 40 10	340 -300 -300 -300 -1000				
PLS21-005	FF10E	\$30C	106	47.6	1655 1968	196.5 196.5 196.5	10 03 60	391-000 429 -300-1000	82	84	72.1	309.8
					101.0 101.0 101.5	150.5 160.5	25 95 299	-300 - 1300 -300 - 750 -300 - 5100				
					205.5 216.0 221.0	297.5 292.5 206.6	20 28 48	-300 - 1930 410 - 750 -300 - 1930				
					278 i 281 i	102.5 107.5 100.5 207.5 202.5 203.5	00 28 20 20 20 20 20 20 20 20 20 20 20 20 20	588 (44.179) 588 (44.179) 588 (44.179) 589 (45.179) 589 (
					2963 3060 3014	206.3 209.3 268.0	10	-300 - 3000 340 - 1000 +300 - 520				
					331.5 321.6	524.9 524.9 208.5	05 05 15	408 640 - 10400 756 - 1600				
					3618 3618 3616	363.5 362.5 379.5	10	430 - 500 430 - 600 400 - 500 330 - 440				
ER2 L606	PENDE	NO.	134	.81.1	377.5 803.6	579.3 579.3 106.3	05 50 51	798 -300 H000 1000 FM	82	No.	01	2713
					9410 1735 2035	168.5 198.3 209.4	27.5 28.5 1.0	-300 - 25400 -300 - 14100 310 - 2301				
					2018 2016 2016	218.8 272.6 264.4	20 45.5	330 - 2100 -300 - 9000 570 - 500*				
					375 818 185 185 940 1735 2018 2018 2019 2015 2010 2015 2010 2015	979.8 106.8 102.8 168.5 198.9 206.8 206.8 272.8 264.9 267.5 266.9	05 30 55 275 285 18 20 405 40 10 10 15	9001 - 0400 510 - 5300 238				
					366.6 356.6 325.6	309.0 347.5 329.5	15	380 - 860 - 900 - 5000				
PLEZIARY	P710E	1066	130	76.6	325.0 96.0 363.6 245.0 246.0 366.0 366.0 365.0 365.0 365.0	329.5 196.0 296.0 295.0 296.0	55 50 28 10 200 05 173 40 10 20	-300 - 3000 -300 - 3000 300 - 740	12	160	N3	304.0
					2966 2965 2866	256.3 256.3 287.5	29-0 0-5 17-0	-300 - 50700 Fall -300 - 5000				
					301.0 312.0 324.0	308.3 363.9 325.9	40 10 20	308 - 6750 950 - 1130 306 - 670				
PLED LIGHT	PERSON	1000	336	.01.1	231.0 10.8 15.5	301.5 189.5 183.9	65 68 75	379 330 - 2400 +300 - 2400	62	164	66.2	363.1
					2310 1038 1755 1850 2810 2810 2815 2315 2315 2315 2315 2310 2310 2310 2310 2310 2310 2310 2310	501.5 100.6 100.6 100.0	05 45 75 00 93 15 20 15 20 15 20 15 20 15 20 15 20 15 20 15 20 15 20 15 20 15 20 15 20 45 20 15 20 16 20 16 20 16 20 16 20 20 16 20 20 20 20 20 20 20 20 20 20	+300 - 540 +300 - 540 +300 - 5300				
					298.6 228.6 238.5	209.8 209.9 209.5	20 15 20	-300 H000 430 - 470 300 - 900				
					2945 2963 2766	250.3 250.3 250.3	45 123 280	-300 - 4750 -300 - 34150 -300 - 20100				
		TOM	301	C5.4	344.5 703.3	109.5 546.9	15	-300 - 3000 600 - 1400 808	12	100	87	309.9
L321-009	F7300	ı -	ľ		2846 2846 2825	298.8 298.9 299.5	21.5 60 60	-300 - 8100 -300 - 1300 -300 - 1900				
1321-009	F7908				276.6 262.5 362.6	279.9 299.5 300.0	99 49 19	-500 - 1900 -500 - 500 430 - 670				
1321-000	F7108					200.0	160	400 1000	9.2			
1321-000	F750E	9150	304	36.1	305.0 145.0 165.0	148.5	40	-300 -490		NA.	66.2	365.9
L321-000 L321-000	F790E	9150	354	-04.1	306.0 146.0 166.0 186.0 201.6 236.0	148.5 172.8 188.8 208.6 208.5	40 190 40 05	-300 - 400 -300 - 3300 -300 - 1400 340			66.2	365.9
5321-000 5521-000	F790E	9190	354	36.1	306.0 946.0 986.0 306.6 236.6 236.0 236.5 246.0	1985 1728 1888 285 295 2915 2918 2918	05 40 190 40 05 05 55 20	-300 - 400 -300 - 3200 -300 - 1400 340 -300 - 15000 -300 - 20000 -300 - 1500		NA.	86.2	363
5321-000 5321-000	F7306	9190	354	-SET	2010 1410 1610 1610 2014 2314 2315 2410 2410 2410 2410 2410 2410 2410 2410	2018 1985 1728 1983 2065 2065 2015 2018 2018 2018 2018 2018 2018	65 40 100 40 65 65 50 20 81 200 100	-300 - 400 -300 - 3300 -300 - 1300 -300 - 1300 -300 - 2000 -300 - 2000 -300 - 2000 -300 - 2000 -300 - 2000		MA.	66.2	365.8
	F730E F730E	9792	504	48.9	306.6 96.6 96.0 301.6 201.6 201.6 201.0 201.0 301.6 301.	98.5 172.8 188.8 266.5 266.5 266.5 266.9 267.8 267.8 267.5 267.5 267.8 269.8 369.8	05 40 100 05 05 05 55 20 20 150 150 150	194 - 194 -	82	NA NA	65.8	365.9
P537-000 P537-000	F790E F790E	9152	561	46.9	2016 9816 9816 2016 2216 2216 2216 2016 2016 2016 20	985 1728 1888 2645 2645 2615 2618 2618 2618 2618 2618 2618 2618 2618	100 05 40 05 40 05 55 20 81 20 150 150 20 20 20 20 20 20 20 20 20 20 20 20 20	-2001-100 -2001-1200 -2001-1200 -5601-15000 -2001-15000 -2001-1500 -2001-1200 -2001-1200 -2001-1200 -2001-1200 -2001-1200 -2001-1200 -2001-1200 -2001-1200 -2001-1200 -2001-1200 -2001-1200 -2001-1200 -2001-1200 -2001-1200		RA RA		365.9

Natural gamma radiation in drill core that is reported in this news release was measured in counts per second (cps) using either a hand-held RS-230 or RS-125 Scintillometer, both manufactured by Radiation Solutions, which are capable of discriminating readings up to 65,535 cps. Natural gamma radiation in the drill hole survey that is reported in this news release was measured in counts per second (cps) using a Mount Sopris 2GHF-1000 Triple Gamma probe, which allows for more accurate measurements in high grade mineralized zones. Triple Gamma probe is preferred in zones of high-grade mineralization. The reader is cautioned that scintillometer readings are not directly or uniformly related to uranium grades of the rock sample measured, and should be used only as a preliminary indication of the presence of radioactive materials. The degree of radioactivity within the mineralized intervals is highly variable and associated with visible pitchblende mineralization. All intersections are down-hole. All depths reported of core interval measurements including radioactivity mineralization intervals widths are representative of true thickness. The orientation of the mineralized intervals tend to follow that of lithologic contacts, and generally dip steeply to the south. Within the Triple R deposit, individual zone wireframe models constructed from assay data and used in the resource estimate indicate that all 5 zones have a complex geometry controlled by and parallel to steeply south-dipping lithological boundaries as well as a preferential sub-horizontal orientation.

Samples from the drill core will be split in half sections on site and where possible, samples will be standardized at 0.5m down-hole intervals. One-half of the split sample will be sent to SRC Geoanalytical Laboratories (an SCC ISO/IEC 17025: 2005 Accredited Facility) in Saskatoon, SK for analysis which includes $\rm U_3O_8$ (wt %) and fire assay for gold, while the other

half remains on site for reference. All analysis includes a 63 element ICP-OES, uranium by fluorimetry and boron.

PLS Mineralized Trend & Triple R Deposit Summary

Uranium mineralization of the Triple R deposit at PLS occurs within the Patterson Lake Conductive Corridor and has been traced by core drilling over ~3.18 km of east-west strike length in five separated mineralized "zones" which collectively make up the Triple R deposit. From west to east, these zones are: R1515W, R840W, R00E, R780E and R1620E. Through successful exploration programs completed to date, Triple R has evolved into a large, near surface, basement hosted, structurally controlled high-grade uranium deposit. The discovery hole was announced on November 05, 2012 with drill hole PLS12-022, from what is now referred to as the R00E zone.

The R1515W, R840W and R00E zones make up the western region of the Triple R deposit and are located on land, where overburden thickness is generally between 55 m to 100 m. R1515W is the western-most of the zones and is drill defined to ~90 m in strike-length, ~68 m across strike and ~220 m vertical and where mineralization remains open in several directions. located ~515 m to the east along strike of R1515W and has a drill defined strike length of ~430 m. ROOE is located ~485 m to the east along strike of R840W and is drill defined to ~115 m in strike length. The R780E zone and R1620E zones make up the eastern region of the Triple R deposit. Both zones are located beneath Patterson Lake where water depth is generally less than six metres and overburden thickness is generally about 50 m. R780E is located ~225 m to the east of R00E and has a drill defined strike length of ~945 m. R1620E is located ~210 m along strike to the east of R780E, and is drill defined to ~185 m in strike length.

The Company completed and filed a prefeasibility "PFS" study on November 07, 2019 titled "Pre-Feasibility Study on the Patterson Lake South Property Using Underground Mining Methods, Northern Saskatchewan, Canada". The report summarizes the Pre-Feasibility Study ("UG PFS"), which outlines an underground-only mining scenario for PLS which to date has only considered the R00E and R780E zones. Further work, including additional drilling may provide sufficient data for future inclusion of the R1515W, R840W and R1620E zones into the Feasibility Study mine plan.

Mineralization along the Patterson Lake Corridor trend remains prospective along strike in both the western and eastern directions. Basement rocks within the mineralized trend are identified primarily as mafic volcanic rocks with varying degrees of alteration. Mineralization is both located within and associated with mafic volcanic intrusives with varying degrees of silicification, metasomatic mineral assemblages and hydrothermal graphite. The graphitic sequences are associated with the PL-3B basement Electro-Magnetic (EM) conductor.

Patterson Lake South Property

The 31,039 hectare PLS project is 100% owned and operated by Fission Uranium Corp. PLS is accessible by road with primary access from all-weather Highway 955, which runs north to the former Cluff Lake mine and passes the nearby Nexgen Arrow deposit located 3km to the east and UEX-Areva Shea Creek discoveries located 50km to the north.

The technical information in this news release has been prepared in accordance with the Canadian regulatory requirements set out in National Instrument 43-101 and reviewed on behalf of the company by Ross McElroy, P.Geol., President and CEO for Fission Uranium Corp., a qualified person.

About Fission Uranium Corp.

Fission Uranium Corp. is a Canadian based resource company specializing in the strategic exploration and development of the Patterson Lake South uranium property - host to the classleading Triple R uranium deposit — and is headquartered in Kelowna, British Columbia. Fission's common shares are listed on the TSX Exchange under the symbol "FCU" and trade on the OTCQX marketplace in the U.S. under the symbol "FCUUF."

ON BEHALF OF THE BOARD

"Ross McElroy"

Ross McElroy, President and CEO

Cautionary Statement:

Certain information contained in this press release constitutes "forward-looking information", within the meaning of Canadian legislation. Generally, these forward-looking statements can be identified by the use of forward-looking terminology such as "plans", "expects" or "does not expect", "is expected", "budget", "scheduled", "estimates", "forecasts", "intends", "anticipates" or "does not anticipate", or "believes", or variations of such words and phrases or state that certain actions, events or results "may", "could", "would", "might" or "will be taken", "occur", "be achieved" or "has the potential to". Forward looking statements contained in this press release may include statements which involve known and unknown risks and uncertainties which may not prove to be accurate. Actual results and outcomes may differ materially from what is expressed or forecasted in these forward-looking statements. Such statements are qualified in their entirety by the inherent risks and uncertainties surrounding future expectations. Among those factors which could cause actual results to differ materially are the following: risks related to the Offering, risks related to Fission's limited business history, risks related to the nature of mineral exploration and development, discrepancies between actual and estimated mineral resources, risks related to uranium market price volatility, risks related to the market value of the common shares of Fission, risks related to market conditions, risks related to the novel coronavirus (COVID-19) pandemic, including disruptions to the Company's business and operational plans, risks related to the global economic uncertainty as a result of the novel coronavirus (COVID-19) pandemic and other risk factors listed from time to time in our reports filed with Canadian securities regulators on SEDAR at www.sedar.com. The forward-looking statements included in this press release are made as of the date of this press release and the Company disclaims any intention or obligation to update or revise any forward-looking statements, whether as a result of new information, future events or otherwise, except as expressly required by applicable securities legislation.

SOURCE Fission Uranium Corp.



For further information: Investor Relations, TF: 877-868-8140, ir@fissionuranium.com, www.fissionuranium.com

Related Links

http://www.fissionuranium.com/